

Site Name : C0002 Hole Name : C0002N Lat. 33° 18.0607'N Long. 136° 38.2029'E Report Date : 21/Nov/2013
Depth : @24:00 4287.5 mBRT 2330.0 mbsf Progress : m Sealed Depth : 1,967.50 mBRT RT.MSL : 28.6 m
Depth : @06:00 4287.5 mBRT 2330.0 mbsf Drilling/Coring/Setting Hrs. : hrs LAST CASING : 20" x 860.30 mbsf(2,827.8 mBRT)
Summary of Operation on 20-Nov : POOH 13-3/8"CSG. Spot LCM mud. Replace PADPRT. Rig up CSG handling tool.
Present Operation @ 06:00 on 21-Nov : Laying down 13-3/8" CSG joints.
Time Breakdown (00:00 - 24:00) on 20-Nov

Table with columns: From, To, Hrs, Code, Detail of Operation. Contains detailed log entries for 20-Nov, including operations like 'Continue circulating at 300gpm', 'Remove SST from CSG hanger joint', and 'Rig up 13-3/8" CSG handling tools'.

Table with columns: LFLJ, LMRP, BOP. Values: LFLJ 0, LMRP 130, BOP 160.

Table with columns: Tantal M, Tantal F, Tel Mica M, Tel Mica F, Tel Plug M, Tel Plug F. Values: Tantal M 7.5, Tantal F 7.5, Tel Mica M 1.0, Tel Mica F 2.2, Tel Plug M 0.3, Tel Plug F 1.5.

Note: ROV - Bulls eyes check. Injected 6gal of glycol to LMRP and BOP. Hydrate formed 40%.
Mud lost in 17" hole section: 36m3/day, 4.18m3/dog.
Sea current @ Chikyu 0.5-1.2 knot. 5mile SW 1.0-3.2 knot.

Table with columns: From, To, Hrs, Code, Detail of Operation. Contains detailed log entries for 21-Nov, including operations like 'Continue rigging up 13-3/8" CSG handling tools' and 'Hold TBRA, start laying down 25ft of 13-3/8" CSG from load#19 to #40'.

Note: Sea current: Chikyu 1.3 knot, 5 mile SW 2.5 knot @ 6:00.

Table with columns: Bit No., Size (in), MFR, Type, IADC Code, S/No., Nozzles, Depth (m), Meter-age, Hrs., WOB (kN), rpm, Total Rev (krev), Inner, Outer, Dull, Loc., B, G, O.D., RP.

Table with columns: Mud Type, Time, Depth (mBRT), MW, VIS, PV, YV, Gel St. (10"/10'), WL, Cake, pH, Pl, Cl-, Sand, Oil, Solid, MBC, Temp (In, Out), K+, n, K, LGS.

Table with columns: No., Liner Size, SPM, GPM, Press. (MPa), Ann. Vel. (min/m), CSG.

Table with columns: Item, Received, Used, Stock. Lists various materials on board such as Barite, Kungite, NaCl, KCl, etc.

Table with columns: No., #10, #180 x 2, No.4, #10, #180 x 2, No.1, 2.5. Lists shale shaker configurations.

Table with columns: Item, Unit, Received, Used, Stock. Lists materials stock on board at 24:00.

Table with columns: Boat Name, Status, Departed, Arrived. Lists boat information for Chikyu, Shingou, etc.

Table with columns: Time, Weather, Temp. (degC), Barometer, Wind, Wave, Current, Visibility. Lists weather information.

Today's Schedule : Continue laying down 13-3/8" CSG, Slip & cut drill line, MU casing hanger joint, run 13-3/8" CSG on landing joints.

Table with columns: Hook Wt. (kN) @, 2307.1 mBRT, 2,985.

Table with columns: Empty, Full, Total. Lists cutting skip information.

Table with columns: Fit, Time, Passenger. Lists heli information.

Table with columns: Incident, Last Incident, 13/Feb/2013, No. LTA. Lists safety information.

Table with columns: Heave (m), Pitch (deg), Roll (deg), Vessel Heading (deg), Riser Tension (kN), V.D. Load (Moon), Max Draught (m), Thruster (kW), Well Cost (1,000 Yen). Lists marine information.

Reported by : S. Kataoka / T. Yokoyama / S. Yamada
Approved by : T. Sanhashi